

+1 713 492 2961 | **T** sales@siriusplastics.com | E www.siriusplastics.com | W

POLYCARBONATE Sheets

PROPERTIES

- Very high impact resistance
- o Up to 88% light transmission (depends on sheet thickness)
- o B s1 d0
- · Outstanding weatherability
- o Easy fabrication
- Cutting with a shear (up to 4 mm)
- o Excellent resistance to dilute acids and mineral oils
- o Optional UV coating on both sides
- o Outstanding sound insulation
- o IR coating available for max light transmission vs min heat transmission
- o UL-94:2017 vertical tested



- * Double side UV coating is available in special orders
- Only Clear sheets are available in Houston warehouse

 Opal, diffuser, translucent colors and IR coating available in special orders

 Any different size for your projects available in special orders

 Special orders are delivered from Turkey in 6 to 8 weeks delivery

NOMINAL	THOMESO	M/ 1	OKID COLINIT
THICKNESS	THICKNESS	WxL	SKID COUNT
1/16"	0.060"	48" x 96"	160
1/12"	0.080"	48" x 96"	120
1/8"	0.118"	48" x 96"	80
1/0	0.125"	48" x 96"	75
-	0.157"	48" x 96"	60
3/16"	0.177"	48" x 96"	45
3/10	0.197"	48" x 96"	45
1/4"	0.220"	48" x 96"	45
1/4	0.236"	48" x 96"	40
3/8"	0.375"	48" x 96"	25
3/0	0.394"	48" x 96"	25
1/2"	0.472"	48" x 96"	20
1/2	0.500"	48" x 96"	20
1/8"	0.118"	72" x 96"	40
-	0.157"	72" x 96"	30
3/16"	0.177"	72" x 96"	40
3/10	0.197"	72" x 96"	25
1/4"	0.220"	72" x 96"	20
1/4	0.236"	72" x 96"	20
1/8"	0.118"	80" x 120"	45
-	0.157"	80" x 120"	35
3/16"	0.177"	80" x 120"	30
3/10	0.197"	80" x 120"	25
1/4"	0.220"	80" x 120"	25
1/4	0.236"	80" x 120"	23
3/8"	0.394"	80" x 120"	14
1/2"	0.472"	80" x 120"	12

APPLICATIONS

- Building: Skydome and skylids
- Roofing: Transparent roofing for airports, stadiums, energy saving applications
- Transparent Indoor Applications: Separators and decoration
- Noise Barriers: On side of roads & highways and public
- Lightening: Safer applications in hospitals, schools, hotels
- Windows for Transportation Vehicle
- Mechanical: Machine safety panels
- Safety Applications: Police shields, security framing

ACRYLIC Sheets

PROPERTIES

- Excellent thermoforming capabilites
- o B2 / Class 4 / UL 94 HB fire rated
- o 92% light transmission
- o Outstanding weatherability
- o High impact resistance
- o Easily fabricated
- o Resistant to inorganic acids
- o Suitable for food contact
- ° Max continuous operating temp. 70°C
- o Max intermittent operating temp. 90°C
- o Diffusing effects available for LED lightening
- o Antiglare effect (P95) for framing





- * Only Clear and 7328 Sign White sheets are available in Houston warehouse
- "Opal, diffuser, translucent colors and IR coating available in special orders
 Any different size for your projects available in special orders
 Special orders are delivered from Turkey in 6 to 8 weeks delivery

NOMINAL THICKNESS	THICKNESS	WxL	SKID COUNT
1/8"	0.118"	48" x 96"	80
170	0.125"	48" x 96"	75
-	0.157"	48" x 96"	60
3/16"	0.177"	48" x 96"	45
57.10	0.197"	48" x 96"	45
1/4"	0.220"	48" x 96"	45
1/4	0.236"	48" x 96"	40
3/8"	0.375"	48" x 96"	25
0/0	0.394"	48" x 96"	25
1/2"	0.472"	48" x 96"	20
1/2	0.500"	48" x 96"	20
1/8"	0.118"	72" x 96"	40
-	0.157"	72" x 96"	30
3/16"	0.177"	72" x 96"	40
3/10	0.197"	72" x 96"	25
1/4"	0.220"	72" x 96"	20
1/4	0.236"	72" x 96"	20
1/8"	0.118"	80" x 120"	45
-	0.157"	80" x 120"	35
3/16"	0.177"	80" x 120"	30
	0.197"	80" x 120"	25
1/4"	0.220"	80" x 120"	25
1/4	0.236"	80" x 120"	23
3/8"	0.394"	80" x 120"	14
1/2"	0.472"	80" x 120"	12



APPLICATIONS

- Architecture & Constructions: Aquaria/structural panels
- Advertising & Visual Communications: Display POS/POP and advertising, museum casings
- Interiors & Household Goods: Appliance parts, gift and
- Lightening: LED back and side lightening applications, light diffusing applications
- Automotive & Transport: Accesories, coatings, caravan windows, acrylic ship windows, windshields

PET-G Sheets

PROPERTIES

- Very high impact resistance & toughness
- o 89% light transmission
- o Excellent transparency & clarity
- o Superior chemical resistance
- o Cost effective
- o Easy to fabricate
- Outstanding thermoforming capabilities
- o Excellent fire resistance
- o Suitable for food contact
- o Can be cut with laser and a shear
- o Surface scratches can easily be removed
- o Max continious operating temp. 65°C
- Max intermittent operating temp 72°C
- o FDA Tested (CFR Title 21 Part 177.1315 Clause B)



NOMINAL THICKNESS	THICKNESS	WxL	SKID COUNT
1/25"	0.040"	48" x 96"	240
1/16"	0.060"	48" x 96"	160
1/12"	0.080"	48" x 96"	120
1/8"	0.118"	48" x 96"	80
	0.125"	48" x 96"	75
-	0.157"	48" x 96"	60
2/16"	0.177"	48" x 96"	45
3/16"	0.197"	48" x 96"	45
1/4"	0.220"	48" x 96"	45
	0.236"	48" x 96"	40
3/8"	0.375"	48" x 96"	25
	0.394"	48" x 96"	25
1/2"	0.472"	48" x 96"	20
	0.500"	48" x 96"	20



APPLICATIONS

- Sign & Display: At hotels, stores, offices
- Interior Design: Partitions, furniture
- Store Fixtures: Modular & individual solutions
- Instrument Panel & Display Screens
- Vending Machines
- Medical: Infant incubators
- Safety: Machine covers, security glazing & visors
- Municipal Propose: For roofing material on bus stop

TWINWALL Sheets

PROPERTIES

- o Very high impact resistance
- · Excellent light transmission
- · Excellent thermal insulation
- One/two side UV coating
- o B s1 d0
- o Outstanding weatherability
- Easy to cut & machine
- o Can be formable with cold bending
- Chemical resistant
- · Sound insulation
- · Light weight
- Hail resistant
- Service temperature 40°C, +120°C
- o IR coating available for max light transmission vs min heat transmission
- o Optional Anti-fog surface









- * Only 48" X 144" Clear sheets are available in Houston warehouse * Double side UV coating and IR coating available in special orders * Opal and translucent colors available in special orders
- * Any different size may be available in special orders
- ecial orders are delivered from Turkey in 6 to 8 weeks



APPLICATIONS

- Architectural Projects
- Canopies
- Vertical Glazing
- Indoor Separators and LED Decoration
- Curved Roof Lights
- Industrial Roof Lights
- Signage

- Indoor Shopping Center
- Greenhouse Coverings
- Swimming Pool Coverings
- Skylights
- Glazing Applications: Skylights, walkaways, windows, shelters

HIPS Sheets

PROPERTIES

- · Cost effective printing
- Outstanding thermoforming characteristics for deep drawn forming
- Good machinability
- o Easy to assemble with adhesives or solvents
- o High impact strength even in low temperatures
- o Higher chemical resistance
- o Easy to paint or print on in digital printing or screening
- o Available in a wide variety of light colors

THICKNESS	WxL	COLOR	SKID COUNT
0.020"	48" x 96"	White	550
0.030"	48" x 96"	White	350
0.040"	48" x 96"	White	280
0.060"	48" x 96"	White	180
0.080"	48" x 96"	White	150
0.100"	48" x 96"	White	120
0.118"	48" x 96"	White	100
0.020"	50" x 99"	White	550
0.030"	50" x 99"	White	350
0.040"	50" x 99"	White	280
0.060"	50" x 99"	White	180
0.080"	50" x 99"	White	150
0.100"	50" x 99"	White	120
0.118"	50" x 99"	White	100

^{*} Matt/Gloss or Matt/Matt options available



APPLICATIONS

- Printing: Digital printing or silk screen printing
- White Goods: Provide high impact strength, good elongation and heat distortion properties
- Furniture: Furniture industry need thermoformable, paintable, impact and chemical resistant
- Automotive: At roof and ski boxes, heavy goods vehicle parts and parts of agricultural machines



^{*} Double side UV coating available in special orders
* Only Clear sheets are available in Houston warehouse
* Any different size for your projects available in special orders

^{*} Opal, diffuser and translucent colors available in special orders

^{*} Special orders are delivered from Turkey in 6 to 8 weeks delivery

^{*} Any special size for your projects may be available in special orders * Special orders are delivered from Turkey in 6 to 8 weeks delivery